



200kVA ENDRESS RENTAL Line generator with electric start

## TEKNISET TIEDOT

|                                    |                                                                                                      |                                        |             |
|------------------------------------|------------------------------------------------------------------------------------------------------|----------------------------------------|-------------|
| <b>Tuotekoodi</b>                  | E333288                                                                                              | <b>No. of motor cylinders and type</b> | 6L          |
| <b>Model</b>                       | John Deere 6068HFG82-B15                                                                             | <b>Nominal voltage V</b>               | 400/230     |
| <b>Measurements L x W x H mm</b>   | 3560x 1190 x 2180                                                                                    | <b>Nimellisvirta 3~ (PRP) A</b>        | 288.7       |
| <b>Weight (kg) ~</b>               | 2664                                                                                                 | <b>Fuel</b>                            | Diesel      |
| <b>Alternator type</b>             | synkroni                                                                                             | <b>Main circuit breaker [Pole]</b>     | 4           |
| <b>Sockets</b>                     | CEE 400V / 63A CEE 400V / 32A CEE 400V / 16A CEE 230V / 16A 230V / 16A<br>Sukopistorasia Klemmleiste | <b>Max. Output [LTP] [kVA/kw]</b>      | 220,0/176,0 |
| <b>Displacement [cm3]</b>          | 6800                                                                                                 | <b>Fuel tank capacity [l]</b>          | 960         |
| <b>Jatkuva teho (PRP) kVA/kW</b>   | 200.0/160.0                                                                                          | <b>Taajuus Hz</b>                      | 50          |
| <b>Fuel cons. at 75% PRP [L/h]</b> | 37.6                                                                                                 | <b>Tehokerroin (Cos theta)</b>         | 0.8         |
| <b>Start-up system</b>             | Sähkökäynnistin                                                                                      | <b>Sound pressure level LPA db(A)</b>  | 96          |