



Abbildung ähnlich /
Illustration similar

253,0kVA ENDRESS POWER Line -generator with electric start

TEKNISET TIEDOT

Tuotekoodi	E331238	Max. Output [LTP] kVA / kW 3 ~	275,0 / 220,0 kVA/kW
Model	Kuusisylinterinen nelitahtinen	Engine output (LTP) kW	228,0kW
Measurements L x W x H mm	3951 x 1438 x 2085	Nominal voltage V	400V 3~ /230V 1~
Weight (kg) ~	2990kg	Nominal current / Cos theta	365,1A 3~ /0,8
Running time at 75% load (h)	13,7h	Continuous power [PRP] kVA / kW 3 ~	253,0 / 202,0 kVA/kW
Insulation	Luokka H	Fuel tank capacity [l]	Diesel / 636
Cooling system	vesijäähdytteinen	Alternator model	Synkroni MeccAlte
Revolutions per minute (rpm) / control	1500/ Electronic	Sound pressure level LPA (7m) db (A)	72 db(A)
Fuel cons. at 75% PRP [L/h]	46,4l	Sound pressure level LPA db(A)	97 db(A)
Volume	7150 cm ³	Frequency / regulation	50 Hz / elektroninen
Start-up system/Battery	Sähkökäynnistin /24V		