

ESE 306 HS-GT

3,4 / 2,9kVA ENDRESS Professional GT Line generator

SKU: E112301



TECHNICAL ATTRIBUTES

Model		Nimellisvirta A	12,5 A
Measurements L x W x H mm	637 x 473 x 500 mm	Fuel	Bensiini
Weight (kg) ~	43 kg	Puutarhatyökälyt (asti)	1300 W
Running time at 75% load (h)	18h	Protection class	23 IP
Shockproof sockets	2 x 230 V/16 A	Fuel tank capacity [l]	20 l
Continuous power	2,9 / 2,6 kVA/kW	Taajuus Hz	50 Hz
Fuel cons. at 75% PRP [L/h]	1,1l	Teho 3000 r/min nopeudella kW	3,3 kW
Volume	196 cm ³	Tehokerroin (Cos theta)	0,9 cos φ
Start-up system	Narukäynnistin	Alternator model	
Possible applications	230 V	Sound pressure level LPA (7m) db (A)	71 db(A)
Max. Ulostulo [LTP] kVA/kW	3,4 / 3,1 kVA/kW	Sound pressure level LPA db(A)	96 db(A)
No. of motor cylinders and type	Yksisylinterinen nelitahtinen OHV	Electric tools up to	1700 W
Nominal voltage V	230 V	Electric devices up to	2500 W