

## ESE 406 HG-GT ISO DUPLEX

4.4/4.0kVA ENDRESS DUPLEXplus Line -generator

SKU: E113552I



### TECHNICAL ATTRIBUTES

<b>Model</b>	Honda GX 270	<b>Nimellisvirta A</b>	17,4 A
<b>Measurements L x W x H mm</b>	780 x 550 x 595 mm	<b>Fuel</b>	Bensiini
<b>Weight (kg) ~</b>	94 kg	<b>Puutarhatyökälyt (asti)</b>	2700 W
<b>Running time at 75% load (h)</b>	20,5h	<b>Protection class</b>	54 IP
<b>Shockproof sockets</b>	2 x 230 V/16 A 1 x CEE 230 V/32 A	<b>Fuel tank capacity [l]</b>	33l
<b>Continuous power</b>	4,0 / 4,0 kVA/kW	<b>Taajuus Hz</b>	50 Hz
<b>Kompressorit ja pumpun enint.</b>	2000 W	<b>Teho 3000 r/min nopeudella kW</b>	4,6 kW
<b>Fuel cons. at 75% PRP [L/h]</b>	1,6l	<b>Tehokerroin (Cos theta)</b>	1 cos φ
<b>Volume</b>	270 cm <sup>3</sup>	<b>Alternator model</b>	Duplex
<b>Start-up system</b>	Narukäynnistin	<b>Sound pressure level LPA (7m) db (A)</b>	64 db(A)
<b>Possible applications</b>	230 V	<b>Sound pressure level LPA db(A)</b>	97 db(A)
<b>Max. Ulostulo [LTP] kVA/kW</b>	4,4 / 4,4 kVA/kW	<b>Electric tools up to</b>	3900 W
		<b>Electric devices up to</b>	4000 W

<b>No. of motor cylinders and type</b>	Yksisylinterinen nelitahtinen	<b>Welding tools up to</b>	2,5 mm ø
<b>Nominal voltage V</b>	230 V		