



46,0/42,0kVA ENDRESS Rental Line RS 20 - 225 kVA -generator

TEKNISET TIEDOT

Tuotekoodi	E333274	No. of motor cylinders and type	4L
Model	Nelisylinterinen nelitahtinen	Engine output (LTP) kW	37,9kW
Measurements L x W x H mm	2300 x 950 x 1500 2300 x 950 x 1500	Nominal voltage V	400V 3~ /230V 1~ 400/230
Weight (kg) ~	1129kg 1129	Nimellisvirta 3~ (PRP) A	60.6
Running time at 75% load (h)	24h	Nominal current / Cos theta	60,6 A 3~ /0,8
Insulation	Class H	Fuel	Diesel
Alternator type	synkroni	Main circuit breaker [Pole]	3
Sockets	CEE 400V / 63A 1x CEE 400V / 32A 1x CEE 400V / 16A 1x CEE 230V / 16A 1x 230V / 16A Sukopistorasia 1x Klemmleiste	Max. Output [LTP] [kVA/kw]	46,0/36,8
Displacement [cm3]	3319	Continuous power [PRP] kVA / kW 3 ~	42,0 / 33,6 kVA/kW
Jatkuva teho (PRP) kVA/kW	42.0/33.6	Fuel tank capacity [l]	200 Diesel / 200
Cooling system	vesijäähdytteinen	Taajuus Hz	50
Revolutions per minute (rpm) / control	1500/ mekaaninen	Tehokerroin (Cos theta)	0.8
Fuel cons. at 75% PRP [L/h]	8.19 8,2l	Alternator model	Synkroni MeccAlte
Volume	3319 cm³	Sound pressure level LPA (7m) db (A)	66 db(A)
Start-up system	Sähkökäynnistin	Sound pressure level LPA db(A)	91 db(A) 91
Start-up system/Battery	Sähkökäynnistin /12V	Frequency / regulation	50 Hz / elektroninen
Max. Output [LTP] kVA / kW 3 ~	46,0 / 36,8 kVA/kW		