



Abbildung ähnlich /  
Illustration similar

506,3kVA ENDRESS POWER Line -generator with electric start

## TEKNISET TIEDOT

|                                               |                                   |                                             |                      |
|-----------------------------------------------|-----------------------------------|---------------------------------------------|----------------------|
| <b>Tuotekoodi</b>                             | E331273                           | <b>Max. Output [LTP] kVA / kW 3 ~</b>       | 557,9 / 445,6 kVA/kW |
| <b>Model</b>                                  | Kuusisylinterinen<br>nelitahtinen | <b>Engine output (LTP) kW</b>               | 441,0kW              |
| <b>Measurements L x W x H mm</b>              | 4400 x 1560 x 2250                | <b>Nominal voltage V</b>                    | 400V 3~ /230V 1~     |
| <b>Weight (kg) ~</b>                          | 4888kg                            | <b>Nominal current / Cos theta</b>          | 730,8A 3~ /0,8       |
| <b>Running time at 75% load (h)</b>           | 7,8h                              | <b>Continuous power [PRP] kVA / kW 3 ~</b>  | 506,3 / 405,0 kVA/kW |
| <b>Insulation</b>                             | Luokka H                          | <b>Fuel tank capacity [l]</b>               | Diesel / 636         |
| <b>Cooling system</b>                         | vesijäähdytteinen                 | <b>Alternator model</b>                     | Synkroni   MeccAlte  |
| <b>Revolutions per minute (rpm) / control</b> | 1500/ Electronic                  | <b>Sound pressure level LPA (7m) db (A)</b> | 80 db(A)             |
| <b>Fuel cons. at 75% PRP [L/h]</b>            | 81,5l                             | <b>Sound pressure level LPA db(A)</b>       | 105 db(A)            |
| <b>Volume</b>                                 | 16 120 cm <sup>3</sup>            | <b>Frequency / regulation</b>               | 50 Hz / elektroninen |
| <b>Start-up system/Battery</b>                | Sähkökäynnistin<br>/24V           |                                             |                      |