



6,6 / 6,0kVA ENDRESS DUPLEX Plus Line generator with electric start

## TEKNISET TIEDOT

|                                        |                                   |                                             |              |
|----------------------------------------|-----------------------------------|---------------------------------------------|--------------|
| <b>Tuotekoodi</b>                      | E113557                           | <b>Nimellisvirta A</b>                      | 8,7 A        |
| <b>Measurements L x W x H mm</b>       | 780 x 550 x 595 mm                | <b>Fuel</b>                                 | Petrol       |
| <b>Weight (kg) ~</b>                   | 113kg                             | <b>Puutarhatyökalut (asti)</b>              | 3200 W       |
| <b>Running time at 75% load (h)</b>    | 15,5h                             | <b>Protection class</b>                     | 54 IP        |
| <b>Shockproof sockets</b>              | 2 x 230 V/16 A 1 x CEE 400 V/16 A | <b>Fuel tank capacity [l]</b>               | 33l          |
| <b>Continuous power</b>                | 6,0 / 4,8 kVA/kW                  | <b>Taajuus Hz</b>                           | 50 Hz        |
| <b>Kompressorit ja pumpput enint.</b>  | 2400 W                            | <b>Teho 3000 r/min nopeudella kW</b>        | 6,4 kW       |
| <b>Fuel cons. at 75% PRP [L/h]</b>     | 2,1l                              | <b>Tehokerroin (Cos theta)</b>              | 0,8 cos φ    |
| <b>Volume</b>                          | 389 cm <sup>3</sup>               | <b>Sound pressure level LPA (7m) db (A)</b> | 60 db(A)     |
| <b>Start-up system</b>                 | Akkuavusteinen sähkökäynnistin    | <b>Sound pressure level LPA db(A)</b>       | 97 db(A)     |
| <b>Possible applications</b>           | 400 V                             | <b>Electric tools up to</b>                 | 4700 W       |
| <b>Max. Ulostulo [LTP] kVA/kW</b>      | 6,6 / 5,3 kVA/kW                  | <b>Electric devices up to</b>               | 4800 W       |
| <b>No. of motor cylinders and type</b> | 1-cylinder 4 -stroke OHV          | <b>Welding tools up to</b>                  | 3,25 mm dia. |
| <b>Nominal voltage V</b>               | 400 V                             |                                             |              |