



8,3/7,0 kVA ENDRESS Professional GT -line generator

## TEKNISET TIEDOT

|                                         |                                                              |                                             |                         |
|-----------------------------------------|--------------------------------------------------------------|---------------------------------------------|-------------------------|
| <b>Tuotekoodi</b>                       | E112308                                                      | <b>No. of motor cylinders and type</b>      | 1-Sylinteri 4-Tahti OHV |
| <b>Model</b>                            | HONDA GX390 / 11 HP                                          | <b>Nominal voltage V</b>                    | 400/230                 |
| <b>Measurements L x W x H mm</b>        | 800 x 538 x 576                                              | <b>Nimellisvirta A</b>                      | 10.1                    |
| <b>Weight (kg) ~</b>                    | 86                                                           | <b>Fuel</b>                                 | Bensiini                |
| <b>Running time at 75% load (h)</b>     | 14.3                                                         | <b>Puutarha- tai rakennuskoneet enint</b>   | 2800W                   |
| <b>Elektroniset kuluttajat enint</b>    | 5500W                                                        | <b>Engine build</b>                         | 0,8/0,9                 |
| <b>Alternator type</b>                  | Synkroni                                                     | <b>Max. output 1~ [kVA/kW]</b>              | 4.9/4.4                 |
| <b>Invertterihitsauskoneet enint</b>    | 3,25mm                                                       | <b>Max. output 3~ [kVA/kW]</b>              | 8,3/6,6                 |
| <b>Sockets</b>                          | 1 x 230 V/16 A, 1 x CEE<br>230 V/16 A, 1 x CEE 400<br>V/16 A | <b>Power tools up to</b>                    | 3700W                   |
| <b>Displacement [cm3]</b>               | 389                                                          | <b>Fuel tank capacity [l]</b>               | 30                      |
| <b>Jatkuva teho 1~ kVA/kW</b>           | 3.5/3.2                                                      | <b>Taajuus Hz</b>                           | 50                      |
| <b>Jatkuva teho 3~ kVA/kW</b>           | 3.5/3.2                                                      | <b>Teho 3000 r/min nopeudella kW</b>        | 6.4                     |
| <b>Kotelointiluokka generaattori IP</b> | 23                                                           | <b>Tehokerroin (Cos theta)</b>              | 0,8/0,9                 |
| <b>Fuel cons. at 75% PRP [L/h]</b>      | 2.1                                                          | <b>Sound pressure level LPA (7m) db (A)</b> | 72                      |
| <b>Start-up system</b>                  | Sähkökäynnistys ja akku                                      | <b>Sound pressure level LPA db(A)</b>       | 97                      |
| <b>Possible applications</b>            | 400V                                                         |                                             |                         |