



8,3 / 7,0kVA ENDRESS Professional GT Line generator

## TEKNISET TIEDOT

|                                     |                                                            |
|-------------------------------------|------------------------------------------------------------|
| <b>Tuotekoodi</b>                   | E112305                                                    |
| <b>Model</b>                        | Honda GX390                                                |
| <b>Measurements L x W x H mm</b>    | 800 x 538 x 576 mm                                         |
| <b>Weight (kg) ~</b>                | 86 kg                                                      |
| <b>Running time at 75% load (h)</b> | 14h                                                        |
| <b>Shockproof sockets</b>           | 1 x 230 V/16 A 1 x<br>CEE 230 V/32 A 1 X<br>CEE 400 V/16 A |
| <b>Continuous power</b>             | 7,0 / 5,6 kVA/kW                                           |
| <b>Fuel cons. at 75% PRP [L/h]</b>  | 2,1l                                                       |
| <b>Volume</b>                       | 389 cm <sup>3</sup>                                        |
| <b>Start-up system</b>              | Drag                                                       |
| <b>Possible applications</b>        | 400 V                                                      |
| <b>Max. Effekt [LTP] kVA/kW</b>     | 8,3 / 6,6 kVA/kW                                           |
| <b>Motortyp</b>                     | Encylindrig 4 takt                                         |
| <b>Spänning</b>                     | 400 V                                                      |

|                                             |              |
|---------------------------------------------|--------------|
| <b>Märkström</b>                            | 10,1 A       |
| <b>Fuel</b>                                 | Bensiini     |
| <b>Trädgårdsredskap</b>                     | 2800 W       |
| <b>Protection class</b>                     | 23 IP        |
| <b>Fuel tank capacity [l]</b>               | 30 l         |
| <b>Frequency [Hz]</b>                       | 50 Hz        |
| <b>Effekt vid 3000 r/min</b>                | 6,4 kW       |
| <b>Tehokerroin (Cos theta)</b>              | 0,8 cos φ    |
| <b>Alternator model</b>                     | Synkron      |
| <b>Sound pressure level LPA (7m) db (A)</b> | 72 db(A)     |
| <b>Sound pressure level LPA db(A)</b>       | 97 db(A)     |
| <b>Electric tools up to</b>                 | 3700 W       |
| <b>Electric devices up to</b>               | 5500 W       |
| <b>Welding tools up to</b>                  | 3,25 mm dia. |

