



10,3 / 8,8kVA ENDRESS DIESEL Line generator with electric start

TEKNISET TIEDOT

Tuotekoodi	E121010	Nominal voltage V	400 V
Model	LOMBARDINI 25LD330	Nimellisvirta A	12,7 A
Measurements L x W x H mm	960 x 641 x 667 mm	Fuel	Diesel
Weight (kg) ~	160kg	Protection class	23 IP
Running time at 75% load (h)	12h	Fuel tank capacity [l]	24l
Shockproof sockets	1 x 230V/16 A 1 x CEE 400V/16 A	Taajuus Hz	50 Hz
Continuous power	8,8 / 7,0 kVA/kW	Teho 3000 r/min nopeudella kW	11,2 kW
Kompressorit ja pumpput enint.	3500 W	Tehokerroin (Cos theta)	0,9 cos φ
Fuel cons. at 75% PRP [L/h]	2,0l	Alternator model	Duplex
Volume	654 cm ³	Sound pressure level LPA (7m) db (A)	80 db(A)
Start-up system	Akkuavusteinen sähkökäynnistys	Sound pressure level LPA db(A)	105 db(A)
Possible applications	400 V	Electric devices up to	6900 W
Max. Ulostulo [LTP] kVA/kW	10,3 / 8,2 kVA/kW	Työmaa- ja puutarhatyökalut (asti)	4700 W
No. of motor cylinders and type	Kaksisylinterinen nelitahtinen	Welding tools up to	4,0 mm ø

